
Technical information

Productnumber: 85935400





Product description

ESD storage trolley with push handle and base made of electrostatically conductive wood fibreboard, edge 7 mm high. Load capacity top shelf 100 kg. Electrostatically conductive version (electrostatic discharge). Suitable for Euro containers of 600x400 mm. Welded steel profile steel, electrostatically conductive, powder coated gray RAL 7015. Equipped with TPE-ESD wheels with precision ball bearing. 2 swivel castors with brake. Complies with EN 1757-3 safety standard for platform trucks.

Specifications

Article arrangement: New

Version: loading surface / HPL plate

Walls: open

Wheels front: 2 castor wheels solid rubber with wheel locks 125 mm

Wheels back: 2 castor wheels solid rubber, 125 mm

Colour: grey

Surface treatment: powdercoating

Internal length (mm): 605 Internal width (mm): 405 Useful height (mm): 400

Weight (kg) 22

Shelf heights: 200/630

Type: Fetra ESD trolley

Material: electrostatically conductive

Floor: closed

Subgroup: ESD trolleys

Euronorm (mm): 600 x 400

Ral colour: 7015 Length (mm): 750 Width (mm): 415 Height (mm): 970

Loading capacity (kg): 250 Type number: 8593540

EAN Code (Gtin) 8719424076844

Scan the QR code for more information









