

Image not found or type unknown.



## Technical information

**Productnumber : 75.346.880.750**



### Product description

Swivel castor made of pressed steel, plate fitting, gray non-elastic thermoplastic tire, plain bearing, wheel Ø 75 mm, 100KG

Wheel: gray non-elastic thermoplastic rubber tire, with polypropylene wheel core, plain bearing, double wheel fixing

Advantages : Versatile wheel for applications on flat surfaces. Dual wheels for high load capacity at low construction height.

Applications: Excellent for static applications under load, such as heavier cabinets, freezers, etc.

Suitable surface: Flat, unobstructed surface.

Suitable environment: Dry and not permanently damp. For light acids and bases.

### Specifications

Article arrangement: New

Version: Ø 75x48 mm

Top: base plate 60x60 mm

Bolt hole: Ø 6.2 mm

Surface treatment: galvanized

Width (mm): 48

Loading capacity (kg): 100

Type number: 346880750

Additional specifications: double wheel

Type: castor wheel

Material: thermo rubber

Hole centres: 42x42 mm

Colour: colorless

Length (mm): 75

Height (mm): 100

Wheel bearing: sliding bearing

Wheels diameter: 75

Scan the QR code for more information



**KRUIZINGA.NL®**  
Opslag- en transportmiddelen

**KRUIZINGA.DE®**  
Lager- und Transportmittel

**KRUIZINGA.FR®**  
Stockage et ressources de transport

**KRUIZINGA.COM®**  
Material handling equipment