
## **Technical information**

Productnumber: 8522601





## **Product description**

Pallet undercarriage as tugger train. This roller platform is made of robust welded profile steel treated with a scratch-free powder coating. The undercarriage rests on two swivel castors with brakes and two fixed castors (200\*50). The load capacity is 1000 kg. The roller platform is equipped with a self-locking drawbar made of flat steel on the fixed wheel side, which can be operated with the foot, and automatically returns to the rest position by means of a gas pressure spring. On the castor side there is a stable coupling bolt with guide mouth and an independent safety lock. This coupling system guarantees the best possible track fidelity. The tractor must have front-wheel steering and a tugger train drawbar! Maximum 5 undercarriages in a train. Maximum train speed 6 km/h. Maximum towing weight 3,000 kg.

## **Specifications**

Article arrangement: New Version: extendible Floor: open construction

Wheels back: 2 wheels, polyurethane, 200\*50 mm, with brake

Colour: blue

Surface treatment: powdercoating Internal length (mm): 1210 Internal width (mm): 810 Platform height (mm): 280

Weight (kg) 50

Additional specifications: price each



Type: Fetra pallet carrier

Material: steel

Wheels front: 2 wheels, polyurethane, 200\*50 mm

Euronorm (mm): 1200 x 800

Ral colour: 5007 Length (mm): 1325 Width (mm): 855 Height (mm): 775

Loading capacity (kg): 1000

Type number: 22601

EAN Code (Gtin) 8719424018189









