

Image not found or type unknown.



## Technical information

**Productnumber : 75.100.542.261**



### Product description

Pneumatic tyre wheel with block tread, roller bearing, Wheel-Ø 260mm, 150KG

Wheel: pneumatic tyre with block tread, with polyamide wheel core, roller bearing,

Advantages: For medium-heavy transport of e.g. shock-sensitive products or on irregular / unpaved surfaces. Low-noise and vibration damping.

Applications: Versatile use for light transport in e.g. offices, warehouses, shops and institutions. Low-noise, impact-resistant and anti-vibration. Swivel castor for light applications. Less suitable for long-term static use under maximum load.

Suitable surfaces: Almost any surface, both indoors and outdoors. Uneven surfaces such as clinkers, damaged floors and near obstacles such as thresholds. Unpaved surfaces.

Suitable environment : Dry and not permanently damp. With weak chemicals.

### Specifications

Article arrangement: New

Version: Ø 260 mm

Bolt hole: Ø 20 mm

Length (mm): 260

Loading capacity (kg): 150

Type number: 100542261

Drive width: 85

Type: air tire

Material: rubber

Colour: red/black

Width (mm): 85

Wheel bearing: roller bearing

Wheels diameter: 260

EAN Code (Gtin) 8719424144574

Scan the QR code for more information



**KRUIZINGA.NL®**  
Opslag- en transportmiddelen

**KRUIZINGA.DE®**  
Lager- und Transportmittel

**KRUIZINGA.FR®**  
Stockage et ressources de transport

**KRUIZINGA.COM®**  
Material handling equipment