



Technical information

Productnumber : 75.146.416.200



Product description

for more information see manual.

Advantages: For medium-heavy transport on flat floors. Low rolling resistance. Relatively insensitive to notches and very wear-resistant. Non-marking tyre, low-noise operation, hygienic.

Applications: Industrial trolleys, material handling in factories, waste containers, transport containers, metal and chemical companies, medium-duty rolling containers, tool trolleys, warehouse trolleys.

Suitable surface: Hard and flat such as tiles, cement and coatings.

Suitable environment: Both indoors and outdoors. With alcohol, glycol, mineral oils and fats.

Specifications

Article arrangement: New

Version: Ø 200 mm

Top: base plate 135x110 mm

Bolt hole: Ø 11 mm

Surface treatment: galvanized

Width (mm): 50

Loading capacity (kg): 400

Wheel bearing: ball bearing

Temperature resistance: -20 / +60°C

Type: castor wheel

Material: polyurethane rolling surface

Hole centres: 105x80 mm

Colour: colorless

Length (mm): 200

Height (mm): 235

Weight (kg) 2

Type number: 754641

EAN Code (Gtin) 8719424013573

Scan the QR code for more information



KRUIZINGA.NL®
Opslag- en transportmiddelen

KRUIZINGA.DE®
Lager- und Transportmittel

KRUIZINGA.FR®
Stockage et ressources de transport

KRUIZINGA.COM®
Material handling equipment